



AN503120JW

LONGES ABSORBEUR D'ÉNERGIE

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Easy to use

· NFC system guarantees traceability



Durability

· High webbing tenacity thanks to its weave and width

Applications

- Javna dela
- Stavba
- Second work / craftman
- Težka industrija
- Lahka industrija
- Vzdrževanje

Certifications and norms



CSA Z259.11-17

Protects against risks



Fall



AN503120JW

LONGES ABSORBEUR D'ÉNERGIE

Fall protection

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Galvanized steel, Polyester
Length (m)	1.2
With connector	yes
Color	Črna-Rumena
Connector (user side)	Small hook, steel, opening 21 mm
SIZE	1,2 m
Ending	2 sewn thimble loops
Connector (structure side)	1 automatic lock hook, steel, opening 65 mm
Lifespan from manufacturing (let)	10
Weight (kg)	1.46
Fall arrest work situations	Vertical movement on a permanent structure, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	4








Fall protection

AN503120JW

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN503120JW	Black-Yellow	1,2 m	AN503120JW	3295249281199	13295249281196	5	1	8.12 kg	44.0 cm	28.0 cm	15.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height