



Hand protection

VE712GR

WORKS IN OILY ENVIRONMENT

Mechanical glove with pesticide protection, ideal for oily and greasy environments



Specific benefits



Hygiene

· Nitrile means no risk of allergies for users



Performance

· The nitrile coating gives people working in oily/greasy environments an excellent grip on the objects they handle

Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Maintenance
- Automotive
- Mining

Certifications and norms



EN 388
3 1 2 1 X



ISO 18889
GR

Risk Protection



Wearing



Hand protection

VE712GR

WORKS IN OILY ENVIRONMENT

Mechanical glove with pesticide protection, ideal for oily and greasy environments

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
2 [0-4] TEAR RESISTANCE
1 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Knitted coated glove
Mechanical Glove Type	Tricot
Coating material and finition	Smooth Nitrile
Coating Level	Palm Coating
Number of Coatings	Single Coated
Gauge	13
Color	Black-Gray
Size	7, 8, 9, 10, 11
Type of conditioning	in individual bags








Safety gloves

VE712GR

WORKS IN OILY ENVIRONMENT

Mechanical glove with pesticide protection, ideal for oily and greasy environments

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
VE712GR07	Black-Grey	07	VE712GR	3295249131678	13295249131675	240	10	11.6 kg	27.2 cm	58.0 cm	50.4 cm
VE712GR08	Black-Grey	08	VE712GR	3295249131685	13295249131682	240	10	12.6 kg	29.0 cm	57.4 cm	49.8 cm
VE712GR09	Black-Grey	09	VE712GR	3295249131692	13295249131699	240	10	13.3 kg	28.8 cm	57.8 cm	49.8 cm
VE712GR10	Black-Grey	10	VE712GR	3295249131708	13295249131705	240	10	14.2 kg	29.0 cm	57.6 cm	48.4 cm
VE712GR11	Black-Grey	11	VE712GR	3295249216184	13295249216181	240	10	16.1 kg	48.6 cm	58.8 cm	29.2 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height