



Hand protection

VENICUTDX0

LONG-LASTING CUT WORK

Level D cut-resistant glove, contact heat resistant up to 250°, ideal for intensive work



Specific benefits



Performance

- The high-performance HEATnocut fiber provides excellent abrasion and cut resistance
- The high-performance HEATnocut fiber provides resistance to contact heat (250° for 15 seconds)

Applications

- Public Works
- Building
- Mining

Certifications and norms



EN 388
4 X 4 2 D



EN 407
X 2 X X X X

ANSI ISEA 105

A4

Risk Protection



Cutting



Wearing



enjoy safety.

Edit 17/11/2024
www.deltaplus-usa.com



Hand protection

VENICUTDX0

LONG-LASTING CUT WORK

Level D cut-resistant glove, contact heat resistant up to 250°, ideal for intensive work

Standards - Details



EN388:2016+A1:2018

4 [0-4] ABRASION RESISTANCE
X [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
D [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Special glove
Glove family	Knitted uncoated glove with leather palm
Mechanical Glove Type	Tricot
Special gloves kind	Knitted with palm leather
Gauge	10
Benefits element	Reach, Vendor pack
Color	Yellow-Grey
Size	9, 10
Type of conditioning	in individual bags








Safety gloves

VENICUTDX0

LONG-LASTING CUT WORK

Level D cut-resistant glove, contact heat resistant up to 250°, ideal for intensive work

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
VECUTDX0GJ09	Yellow-Grey	09	VENICUTDX0	3295249157289	13295249157286	60	12	10.2 kg	28.0 cm	35.0 cm	37.0 cm
VECUTDX0GJ10	Yellow-Grey	10	VENICUTDX0	3295249157296	13295249157293	60	12	11.3 kg	28.0 cm	35.0 cm	37.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height