



VENICUT52

LANGDURIG WERKEN MET SNIJRISICO

Handbescherming



Toepassing

- Openbare werken
- Bouw & Constructie
- Afwerking / ambachtslieden
- Onderhoud
- Automotive
- Tijdelijk werk

Certificeringen en normen



EN 388
3 X 4 2 D



EN 407
X 2 X X X X

ANSI ISEA 105

A3

Beschermt tegen



Warmte



Snijden



Schuren en slijtage



VENICUT52

LANGDURIG WERKEN MET SNIJRISICO

Handbescherming

Normen - Details



EN388:2016+A1:2018

3 [0-4] SCHUURWEERSTAND
X [0-5] WEERSTAND TEGEN SNIJDEN
4 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
D [A-F] CUT RESISTANCE ISO 13997

Technische details

Type handschoen	Mechanische handschoen
Handschoenfamilie	Gebreide handschoen met coating
Type mechanische handschoen	Gebreid
Coatingmateriaal en afwerking	Gripvaste getextureerde latex
Coatingniveau	Palm coating
Aantal coatings	Enkele coating
Jauge	10
Kleur	Geel-Zwart
Grootte	7, 8, 9, 10








VENICUT52

LONG-LASTING CUT WORK

Safety gloves

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
VECUT5207	Yellow-Black	07	VENICUT52	0	0	60	12	8.3 kg	28.0 cm	34.8 cm	38.4 cm
VECUT5208	Yellow-Black	08	VENICUT52	0	0	60	12	8.9 kg	28.6 cm	34.8 cm	39.2 cm
VECUT5209	Yellow-Black	09	VENICUT52	0	0	60	12	9.4 kg	29.2 cm	37.4 cm	39.4 cm
VECUT5210	Yellow-Black	10	VENICUT52	0	0	60	12	10.0 kg	28.8 cm	37.2 cm	40.2 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height