

AN503180JW

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Fall protection



Specific benefits



 \cdot Can wash harnesses and textiles with neutral soap



 $\cdot\,\text{NFC}$ system guarantees traceability



 \cdot High webbing tenacity thanks to its weave and width

Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Heavy Industry
- Light Industry
- Maintenance

Certifications and norms

ANSI Z359.13-2013 (R2022)



CSA Z259.11-17

Risk Protection







Edit 08/11/2024 www.deltaplus-usa.com



AN503180JW

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Fall protection

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard						
Composition of the main support	Galvanized steel, Polyester						
Length (m)	1.8						
With connector	yes						
Color	Black-Yellow						
Connector 1	Small hook, steel, opening 21 mm						
SIZE	1,8 m						
Ending	2 sewn thimble loops						
Connectors (structure side)	1 automatic lock hook, steel, opening 65 mm						
Lifespan from manufacturing (years)	10						
Weight (kg)	1.7						
Type of conditioning	Box of 5						
Fall arrest work situations	Vertical movement on a permanent structure, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)						
Lenght (ft)	6						



enjoy so



AN503180JW

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Fall protection

	Logistics information												
F	Reference	Colour	Size	Designation	EAN13	Box code		â	Weight				
AN50	03180JW	Black-Yellow	1,8 m	AN503180JW	3295249219505	13295249219502	5	1	8.9 kg	44.0 cm	28.0	15.0 cm	



ſ

Multiple sales

Minimum sales



👕 Box Depth

🗍 Box Height



enjoy sa